



Description

To be used for locating fixtures and clamping elements onto machine tables with T-slots to DIN 650.

Material:

·steel, case-hardened, blackened, ground.

Characteristics:

·for size 20 refer to HG33.1006.2000;

·type 1: size 10-12;

·type 2: size 14-18;

·type 3: size 22-36;

·L in the table represents the slot size of the machine ;

·x in the table represents for which screws (ISO 4762) the fixed guide stone is suitable.

Article Code	L	x	L1	L2	L3	L4	L5	Type	Material
HG30.2006.1000	10	M6 x 10	20	22	10	5,5	12	1	Steel
HG30.2006.1200	12	M6 x 10	20	22	10	5,5	12	1	Steel
HG30.3006.1400	14	M6 x 10	20	25	10	5,5		2	Steel
HG30.3006.1600	16	M6 x 10	20	25	10	5,5		2	Steel
HG30.3006.1800	18	M6 x 10	20	25	10	5,5		2	Steel
HG30.4006.2200	22	M6 x 16	20	32	12	5,5		3	Steel
HG30.4006.2400	24	M6 x 16	20	32	12	5,5		3	Steel
HG30.4006.2800	28	M6 x 16	20	32	12	5,5		3	Steel
HG30.4006.3600	36	M6 x 16	20	32	12	5,5		3	Steel

