



Description

For combination with ball-headed grub screws BG03.

Material:

·thermoplastic (POM), black, dull.

Characteristics:

- temperature range from a minimum of 30°C to a maximum of 80°C;
- d1 in the table is the threaded end with ball-headed grub screws (BG03);
- F1kN in the table is the maximum load capacity for static load.

Article Code	D	d	D1	d1	L	L1	L2	L2	F1(kN)	Material
BG12.0645.0150	15	4,5	8,6	M6	7,6	2,5	4,0	4,0	3,5	POM
BG12.0845.0150	15	6,1	8,6	M8	7,6	2,5	3,0	3,0	3,5	POM
BG12.0845.0180	18	6,1	11,0	M8	9,2	2,5	4,0	4,0	3,5	POM
BG12.1045.0180	18	7,8	11,0	M10	9,2	2,5	3,0	3,0	3,5	POM
BG12.0845.0210	21	6,1	13,0	M8	10,0	3,0	5,0	5,0	3,5	POM
BG12.1045.0210	21	7,8	13,0	M10	10,0	3,0	4,0	4,0	3,5	POM
BG12.1245.0210	21	9,4	13,0	M12	10,0	3,0	3,0	3,0	3,5	POM
BG12.0845.0250	25	6,1	13,0	M8	11,0	3,0	6,0	6,0	3,5	POM
BG12.1045.0250	25	7,8	13,0	M10	11,0	3,0	5,0	5,0	3,5	POM
BG12.1245.0250	25	9,4	13,0	M12	11,0	3,0	4,0	4,0	3,5	POM
BG12.0845.0320	32	6,1	14,0	M8	11,0	3,0	6,0	6,0	3,5	POM
BG12.1045.0320	32	7,8	14,0	M10	11,0	3,0	5,0	5,0	3,5	POM
BG12.1245.0320	32	9,4	14,0	M12	11,0	3,0	4,0	4,0	3,5	POM
BG12.0845.0400	40	6,1	16,0	M8	13,0	4,0	8,0	8,0	3,5	POM
BG12.1045.0400	40	7,8	16,0	M10	13,0	4,0	7,0	7,0	3,5	POM
BG12.1245.0400	40	9,4	16,0	M12	13,0	4,0	6,0	6,0	3,5	POM

