



## Description

### Material:

- knob:** reinforced polyamide (PA-GF); oils and greases resistant;
- insert:** brass/ zinc plated steel blind threaded hole (tolerance 6H).

### Characteristics:

- surface:** satin;
- color:** black (RAL 9011);
- temperature range from a minimum of -20°C to a maximum of 135°C.

### Special request:

It is possible to supply colours for the 3 lobe handwheel as shown in the table on request and for quantities.

Article Code	D	d	D1	d1	L	L1	L2	L3	I	I1	Material
AB57.1037.0450	45	M10	16,0	11,0	21	11,0	10,0	18,0	10	1,0	PA-GF / Brass
AB57.0637.0450	45	M6	16,0	11,0	21	11,0	10,0	18,0	9	1,0	PA-GF / Brass
AB57.0837.0450	45	M8	16,0	11,0	21	11,0	10,0	18,0	11	1,0	PA-GF / Brass
AB57.1037.0650	65	M10	22,0	15,5	28	16,5	11,5	23,5	11	1,5	PA-GF / Brass
AB57.1237.0650	65	M12	22,0	15,5	28	16,5	11,5	23,5	13	1,5	PA-GF / Brass
AB57.0837.0650	65	M8	22,0	15,5	28	16,5	11,5	23,5	11	1,5	PA-GF / Brass
AB57.1037.0850	85	M10	30,0	21,0	37	21,0	16,0	30,5	14	2,0	PA-GF / Brass
AB57.1237.0850	85	M12	30,0	21,0	37	21,0	16,0	30,5	19	2,0	PA-GF / Brass
AB57.0837.0850	85	M8	30,0	21,0	37	21,0	16,0	30,5	15	2,0	PA-GF / Brass
AB57.1037.1050	105	M10	35,0	25,0	46	26,0	19,0	37,5	17	2,0	PA-GF / Brass
AB57.1237.1050	105	M12	35,0	25,0	46	26,0	19,0	37,5	17	2,0	PA-GF / Brass
AB57.1437.1050	105	M14	35,0	25,0	46	26,0	19,0	37,5	19	2,0	PA-GF / Brass
AB57.0837.1050	105	M8	35,0	25,0	46	26,0	19,0	37,5	15	2,0	PA-GF / Brass
AB57.1237.1250	125	M12	42,5	28,5	54	31,0	23,0	44,0	18	2,0	PA-GF / Brass
AB57.1437.1250	125	M14	42,5	28,5	54	31,0	23,0	44,0	18	2,0	PA-GF / Brass
AB57.1639.1250	125	M16	42,5	28,5	54	31,0	23,0	44,0	21	2,0	PA-GF / Steel
AB57.1839.1250	125	M18	42,5	28,5	54	31,0	23,0	44,0	21	2,0	PA-GF / Steel