



Description

Material:

- handwheel: aluminium, permanent-mould casting;
- handle (AF39): thermosetting plastic (PF 31) DIN 7708, black (RAL 9005);
- axle part: steel, galvanized.

Characteristics:

- hub machined;
- rim turned and mirror-finished on all sides;
- non-machined surfaces cleanly blasted;
- together with the mirror-polished rim these handwheels are therefore showing a finish which in most cases does not require additional lacquering;
- shaftend washers CI50 for axial fastening;
- temperature range up to a maximum of 110°C;
- type 1: without keyway, with cylindrical handle; type 2: with keyway, with cylindrical handle.

Article Code	D	d	l	D1	L	L1	I1	I2	Type	Material
Al39.1223.1250	125	12	18	31	33	15,0			1	Aluminum
Al39.1223.1251	125	12	18	31	33	15,0	4	13,8	2	Aluminum
Al39.1423.1250	125	14	18	31	33	15,0			1	Aluminum
Al39.1423.1251	125	14	18	31	33	15,0	5	16,3	2	Aluminum
Al39.1423.1400	140	14	19	36	36	16,5			1	Aluminum
Al39.1423.1401	140	14	19	36	36	16,5	5	16,3	2	Aluminum
Al39.1623.1400	140	16	19	36	36	16,5			1	Aluminum
Al39.1623.1401	140	16	19	36	36	16,5	5	18,3	2	Aluminum
Al39.1423.1600	160	14	20	36	39	18,0			1	Aluminum
Al39.1423.1601	160	14	20	36	39	18,0	5	16,3	2	Aluminum
Al39.1623.1600	160	16	20	36	39	18,0			1	Aluminum
Al39.1623.1601	160	16	20	36	39	18,0	5	18,3	2	Aluminum
Al39.1823.2000	200	18	24	42	45	20,5			1	Aluminum
Al39.1823.2001	200	18	24	42	45	20,5	6	20,8	2	Aluminum
Al39.2023.2000	200	20	24	42	45	20,5			1	Aluminum
Al39.2023.2001	200	20	24	42	45	20,5	6	22,8	2	Aluminum
Al39.2223.2500	250	22	28	48	51	23,0			1	Aluminum
Al39.2223.2501	250	22	28	48	51	23,0	6	24,8	2	Aluminum
Al39.2623.2500	250	26	28	48	51	23,0			1	Aluminum
Al39.2623.2501	250	26	28	48	51	23,0	8	29,3	2	Aluminum