



Description

Strain relief which securely anchors the cable into the device when entering the chassis. The strain relief is clamped tightly around the cable, mounting pliers are available on request. Provides a cost-effective simple assembly that absorbs pressure, pulling and turning forces.

Material:

·strain relief: Nylon (PA 6.6).

Characteristics:

- this strain relief is suitable for a round cable;
- if you would like to install a different cable size, request a sample first;
- this product is UL / CSA certified, file E15331 for UL and file LR-8919 for CSA;

Article Code	D	L1	d	l	L	Color	Material
EF18.3240.1200	12,0-15,2	1,9-3,2	21,6	21,3	20,6	black	PA
EF18.2540.1270	6,2-7,4	1,8-2,5	13,0	11,5	11,0	black	PA
EF18.1640.1590	7,4-8,2	0,5-1,6	15,9	14,0	14,8	black	PA
EF18.3240.1590	7,4-8,2	1,9-3,2	15,9	14,0	14,8	black	PA
EF18.1640.1591	8,2-9,2	0,5-1,6	15,9	14,0	14,8	black	PA
EF18.3240.1591	8,2-9,2	1,9-3,2	15,9	14,0	14,8	black	PA
EF18.7240.1500	9,2-10,5	1,0-3,2	28,0	25,5	25,2	black	PA
EF18.3240.0920	9,2-10,5	1,9-3,2	19,7	17	19,0	black	PA
EF18.2340.1270	7,6	1,8-2,3	12,7	11,8	11,0	black	PA