



Description

Developed for securing screws, bolts and nuts. They prevent loose vibrations, rust and electrolytic corrosion through impeccable double sealing and insulation. Sound and vibration dampening and prevent leakage. These locking washers are often equipped with anti-loss lips (AV lip) so that pre-assembly is possible. Handy for difficult to assemble applications.

Material:

-washer: Nylon (PA).

Characteristics:

-a in the table indicates for which size the spring washer is suitable.

Article Code	d1	D	L	a	Material
CI13.0240.0500	2,1	5,0	1,7	M20,0	PA
CI13.0240.0601	2,5	6,0	2,2	M2,5	PA
CI13.0340.0800	3,1	8,0	2,5	M3,0	PA
CI13.0440.0800	4,2	8,0	2,5	M4,0	PA
CI13.0440.1000	4,2	10,0	2,8	M4,0	PA
CI13.0540.1000	5,2	10,0	2,8	M5,0	PA
CI13.0540.1070	5,2	10,0	3,0	M5,0	PA
CI13.0640.1070	6,2	10,7	3,0	M6,0	PA
CI13.0640.1270	6,2	12,7	3,8	M6,0	PA
CI13.0840.1400	8,2	14,0	3,7	M8,0	PA
CI13.0840.1620	8,2	16,2	4,2	M8,0	PA
CI13.1040.1600	10,2	16,0	4,2	M10,0	PA
CI13.1040.2000	10,2	20,0	5,0	M10,0	PA
CI13.1240.2000	12,2	20,0	5,0	M12,0	PA
CI13.1240.2400	12,2	24,0	5,2	M12,0	PA
CI13.1440.2200	14,2	22,0	5,5	M14,0	PA
CI13.1440.2600	14,2	26,0	5,6	M14,0	PA
CI13.1640.2500	16,2	25,0	6,0	M16,0	PA
CI13.1640.3000	16,2	30,0	5,9	M16,0	PA
CI13.2040.3600	20,3	36,0	6,8	M20,0	PA