




Description

Material:

- handwheel:** reinforced and stabilised polyamide, oils and greases resistant, black (RAL 9011);
- insert:** zinc plated steel insert with smooth through-hole (H10 tolerance);
- side insert for handle:** brass right through threaded bush.

Characteristics:

- alternative cap colour:** orange (RAL 2004); blue (RAL 5015); yellow (RAL 1021); red (RAL 3000); green (RAL 6024); black (RAL 9011); contact us for more information;
- satin surface;
- centra cap colour:** grey PA (RAL 7035);
- d3 in the table is the maximum size of the hole (d);
- temperature range from a minimum of -20°C up to a maximum of 135°C.

Special requests:

For fixing system, execution of keyway or square holes, please refer to the technical notes attached to the documentation.

Article Code	D	d	D1	d1	d2	d3	L	L1	L2	L3	I1	I2	Material
AI19.0539.0810	81	5	25	16	M06	12	33	16,0	17,0	29	9	20	PA-GF
AI19.0539.1000	100	5	30	16	M06	16	39	18,5	20,5	34	10	24	PA-GF
AI19.0539.1250	125	5	36	26	M08	18	44	20,0	24,0	37	13	24	PA-GF
AI19.0839.1500	150	8	38	26	M10	22	54	25,0	29,0	44	12	32	PA-GF
AI19.0839.1730	173	8	40	26	M10	22	57	25,5	31,5	47	15	32	PA-GF
AI19.0839.2020	202	8	44	27	M10	28	59	24,0	35,0	49	13	36	PA-GF
AI19.0839.2490	249	8	59	36	M10	28	68	29,0	39,0	58	22	36	PA-GF