



Description

Material:

·body: case hardened steel, annealed;

·pin: steel.

Characteristics:

- ·attention: If Expander sealing plug with pull-anchor are applied to separate grooves, the admissible working pressure at the setting side has to be halved;
- $\cdot \text{Expander sealing plugs are used for safe, quick and economic sealing of bore holes in fluid technology};\\$
- ·assembly is made by means of user friendly assembly devices;
- body and pin are pre-assembled (suitable for automated processing);
- ·please refer to the technical data following these product information pages.

			L	L1	L2	L3 Material
4	2,50	4	4,5	69	6,5	9 Steel
5	3,00	5	5,5	71	7,5	10 Steel
6	3,40	6	6,5	73	8,0	12 Steel
7	4,10	7	7,5	68	9,0	14 Steel
8	4,20	8	8,5	70	10,5	15 Steel
9	4,50	9	9,5	73	11,0	17 Steel
10	4,75	10	10,5	75	12,5	19 Steel
	5 6 7 8 9	5 3,00 6 3,40 7 4,10 8 4,20 9 4,50	5 3,00 5 6 3,40 6 7 4,10 7 8 4,20 8 9 4,50 9	5 3,00 5 5,5 6 3,40 6 6,5 7 4,10 7 7,5 8 4,20 8 8,5 9 4,50 9 9,5	5 3,00 5 5,5 71 6 3,40 6 6,5 73 7 4,10 7 7,5 68 8 4,20 8 8,5 70 9 4,50 9 9,5 73	5 3,00 5 5,5 71 7,5 6 3,40 6 6,5 73 8,0 7 4,10 7 7,5 68 9,0 8 4,20 8 8,5 70 10,5 9 4,50 9 9,5 73 11,0