



## Description

This galvanized steel locknut is provided with a plastic insert. The insert has a self-locking action, so that the connection remains guaranteed in case of vibrations. From M3 for electronic connections to M20 for strong mechanical fixings. According to DIN 985 standard.

### Material:

·nut: untreated steel; SST.

Article Code	d1	L	SW	Material
CH10.3507.0000	M10	10,0	17,0	Steel
CH10.3515.0000	M10	10,0	17,0	SST
CH10.3807.0000	M12	12,0	19,0	Steel
CH10.3815.0000	M12	12,0	19,0	SST
CH10.4015.0000	M14	14,0	22,0	SST
CH10.4207.0000	M16	16,0	24,0	Steel
CH10.4215.0000	M16	16,0	24,0	SST
CH10.1507.0000	M2	2,5	4,5	Steel
CH10.1807.0000	M2,5	3,8	5,0	Steel
CH10.1815.0000	M2,5	3,8	5,0	SST
CH10.4815.0000	M20	20,0	30,0	SST
CH10.2007.0000	M3	4,0	5,5	Steel
CH10.2015.0000	M3	4,0	5,5	SST
CH10.2507.0000	M4	5,0	7,0	Steel
CH10.2515.0000	M4	5,0	7,0	SST
CH10.2807.0000	M5	5,0	8,0	Steel
CH10.2815.0000	M5	5,0	8,0	SST
CH10.3007.0000	M6	6,0	10,0	Steel
CH10.3015.0000	M6	6,0	10,0	SST
CH10.3207.0000	M8	8,0	13,0	Steel
CH10.3215.0000	M8	8,0	13,0	SST