




Type 1



Type 2



Type 3



Type 4

Description

Pins with plastic contact surface can be used as protective supports, stops, and thrust pads. This protects high-quality surfaces from damage.

Material:

- insert: plastic (PEEK), blue;
- threaded bushing: SST;
- threaded pin: SST;
- body: plastic (PEEK), blue; SST (1.4305).

Characteristics:

- M(Nm) in de table stands for the maximum tightening torque;
- temperature range for the PEEK from a minimum -60°C to a maximum of 250°C ;
- for type 4 is the tightening torque of bolts with female thread quality 8, the bolt has to be tightened over the total thread length.

Article Code	D1	L1	d	l	D2	D	L	F1(kN)	M	SW	SW1	Type	Material
HG62.1915.2003			M10	10	19,0	21,5	20	2,4	10	19	3		SST / PEEK
HG62.1915.3004			M10	15	14,5	21,9	30	3,8	32	19	4		SST / PEEK
HG62.2215.2003			M12	12	22,0	25,0	20	3,4	10	22	3		SST / PEEK
HG62.2215.3004			M12	18	17,5	25,2	30	5,5	60	22	4		SST / PEEK
HG62.1715.1503			M8	9	17,0	19,0	15	2,1	10	17	3		SST / PEEK
HG62.1715.2504			M8	12	12,5	19,4	25	2,8	18	17	4		SST / PEEK
HG62.1915.2001	M10	10			19,0	21,5	20	2,4	10	19	5	1	SST / PEEK
HG62.1915.1002	M10	12			14,5	21,9	10	3,8	32	19	2		SST / PEEK
HG62.1915.1502	M10	12			14,5	21,9	15	3,8	32	19	2		SST / PEEK
HG62.2215.1002	M12	14			17,5	25,2	10	5,5	60	22	2		SST / PEEK
HG62.2215.1502	M12	14			17,5	25,2	15	5,5	60	22	2		SST / PEEK
HG62.2215.2001	M12	14			22,0	25,0	20	3,4	10	22	6	1	SST / PEEK
HG62.1715.1501	M8	8			17,0	19,0	15	2,1	10	17	4	1	SST / PEEK
HG62.1715.1002	M8	10			12,5	19,4	10	2,8	18	17	2		SST / PEEK