



Description

For quick fastening, locking, adjusting, changing and securing. Quickly and easily unlockable for frequently repeated connections.

Material:

- **pin part:** stainless steel 303 (1.4305);
- **handle:** thermoplastic (PA 6), grey;
- **spring:** stainless steel.

Characteristics:

- all versions are corrosion resistant;
- version with ergonomic grip;
- mounting option for fixing cable (AP12);
- for use bores H11 are adequate;
- bore H11 is equal to dimension D1 in the table;
- as an accessory locating bushes (AP11) are available;
- F(kN) in the table stands for the minimal shearing resistance, double;
- F1(N) in the table stands for the tensile force, unlubricated;
- type 1: dimensions D1 = 6 + 8; type 2: dimensions D1 = 10 + 12;
- temperature range from -30°C up to 80°C.

Security note:

Balls are spring-loaded and not locked as in article groups AP01, AP03, AP05, AP08 and AP09.

Article Code	D1	L1	D	D2	D3	L	L2	L3	F(kN)	F1(N)	Type	Material
AP10.0615.0100	6	10	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0615.0150	6	15	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0615.0200	6	20	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0615.0250	6	25	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0615.0300	6	30	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0615.0500	6	50	38	6,5	17,3	27,0	5,0	10,8	22	8	1	SST
AP10.0815.0150	8	15	38	8,7	17,3	28,6	6,3	10,8	40	15	1	SST
AP10.0815.0200	8	20	38	8,7	17,3	28,6	6,3	10,8	40	15	1	SST
AP10.0815.0250	8	25	38	8,7	17,3	28,6	6,3	10,8	40	15	1	SST
AP10.0815.0300	8	30	38	8,7	17,3	28,6	6,3	10,8	40	15	1	SST
AP10.0815.0500	8	50	38	8,7	17,3	28,6	6,3	10,8	40	15	1	SST
AP10.1015.0150	10	15	38	12,0	17,3	28,6	8,7	10,8	62	30	2	SST
AP10.1015.0200	10	20	38	12,0	17,3	28,6	8,7	10,8	62	30	2	SST
AP10.1015.0250	10	25	38	12,0	17,3	28,6	8,7	10,8	62	30	2	SST
AP10.1015.0300	10	30	38	12,0	17,3	28,6	8,7	10,8	62	30	2	SST
AP10.1015.0500	10	50	38	12,0	17,3	28,6	8,7	10,8	62	30	2	SST
AP10.1215.0200	12	20	38	14,5	17,3	28,6	9,5	10,8	90	32	2	SST
AP10.1215.0300	12	30	38	14,5	17,3	28,6	9,5	10,8	90	32	2	SST
AP10.1215.0400	12	40	38	14,5	17,3	28,6	9,5	10,8	90	32	2	SST
AP10.1215.0500	12	50	38	14,5	17,3	28,6	9,5	10,8	90	32	2	SST