



Description

Material:

·handle: reinforced polyamide, oils and greases resistant;

·insert: black-oxide threated steel revolving and folding mechanism with head for screwdriver fitting; stainless steel revolving and folding mechanism (AISI

303) with head for screwdriver fitting.

·spring: steel; stainless steel.

Characteristics:

·surface: satin;

·colour: black;

·temperature range from a minimum of -30°C to a maximum of 135°C.

Special request:

It is possible to supply the revolving and folding handle in colours as shown in the table, on request and for quantities.

Article Code	D	L	D1	D2	L1	L2	sw	F(N)	Туре	Material
AF34.0638.0490	20	49	M6	15	9	5,0	10	270	2	PA-GF / SST
AF34.0639.0490	20	49	M6	15	9	5,0	10	270	2	PA-GF / Steel
AF34.0838.0690	25	69	M8	19	10	6,5	13	840	2	PA-GF / SST
AF34.0839.0690	25	69	M8	19	10	6,5	13	840	2	PA-GF / Steel
AF34.1038.0810	26	81	M10		15	8,0	17	1700	1	PA-GF / SST
AF34.1039.0810	26	81	M10		15	8,0	17	1700	1	PA-GF / Steel
AF34.1038.0890	26	89	M10		15	8,0	17	2700	1	PA-GF / SST
AF34.1039.0890	26	89	M10		15	8,0	17	2700	1	PA-GF / Steel