



Description

Material:

- housing: steel, galvanized;
- cap: steel, galvanized;
- ball: stainless steel.

Characteristics:

- as from D1 = 36 fitted with an oil drenched felt seal to protect against dirt;
- BF02.1207.0000, BF02.1807.0000 and BF02.2407.0000 are without felt seal;
- D in the table is the diameter of the ball;
- D3 in the table is bore of the location hole; reference value for 2 mm sheet steel/ 5 mm aluminium (force fit);
- F1(N) in table indicates the static load.

Article Code	D1	D	D2	D3	L	L1	L2	L3	F1(N)	Material
BF02.1207.0000	12,6 ±0,055	8	17	12,57 +0,03	11,2	4,8 ±0,15	1,8	3,2	70	Steel / SST
BF02.1807.0000	18,0 ±0,055	12	23	17,97 +0,03	15,5	7,4 ±0,15	2,0	4,3	180	Steel / SST
BF02.2407.0000	24,0 ±0,065	15	31	23,95 +0,05	21,5	9,5 ±0,20	2,5	6,1	370	Steel / SST
BF02.3607.0000	36,0 ±0,080	22	45	35,90 +0,05	29,5	9,8 ±0,20	2,9	5,7	970	Steel / SST
BF02.4507.0000	45,0 ±0,080	30	55	44,85 +0,05	37,5	13,8 ±0,30	3,7	7,9	1900	Steel / SST
BF02.6207.0000	62,0 ±0,095	45	75	61,83 +0,07	53,7	19,0 ±0,40	4,2	10,3	4500	Steel / SST