



Description

Material:

- handle: reinforced polyamide (PA-GF);
- insert: zinc plated steel threaded stud (tolerance 6g).

Characteristics:

- surface: satin;
- colour: black;
- temperature range from a minimum of -30°C to a maximum of 135°C.

Special request:

It is possible to supply the handle with threaded stud in colours as shown in the table, on request and for quantities.

Article Code	D1	L	D	D2	L1	Material
AF20.1039.0600	M10	60	23	17,5	15	PA-GF / Steel
AF20.1039.0810	M10	80	26	21,0	10	PA-GF / Steel
AF20.1039.0811	M10	80	26	21,0	20	PA-GF / Steel
AF20.1039.0812	M10	80	26	21,0	30	PA-GF / Steel
AF20.1039.0900	M10	90	27	22,0	10	PA-GF / Steel
AF20.1039.0901	M10	90	27	22,0	20	PA-GF / Steel
AF20.1039.0902	M10	90	27	22,0	30	PA-GF / Steel
AF20.1239.0900	M12	90	27	22,0	20	PA-GF / Steel
AF20.1239.0901	M12	90	27	22,0	30	PA-GF / Steel
AF20.1239.0902	M12	90	27	22,0	40	PA-GF / Steel
AF20.1239.1110	M12	109	32	27,0	20	PA-GF / Steel
AF20.1239.1111	M12	109	32	27,0	40	PA-GF / Steel
AF20.1439.1110	M14	109	32	27,0	20	PA-GF / Steel
AF20.1439.1111	M14	109	32	27,0	40	PA-GF / Steel
AF20.0439.0270	M4	27	14	10,0	20	PA-GF / Steel
AF20.0539.0270	M5	27	14	10,0	20	PA-GF / Steel
AF20.0539.0400	M5	40	18	15,5	20	PA-GF / Steel
AF20.0639.0270	M6	27	14	10,0	20	PA-GF / Steel
AF20.0639.0400	M6	40	18	15,0	10	PA-GF / Steel
AF20.0639.0401	M6	40	18	15,0	20	PA-GF / Steel
AF20.0839.0400	M6	40	18	15,0	25	PA-GF / Steel
AF20.0639.0500	M6	50	20	15,0	10	PA-GF / Steel
AF20.0639.0501	M6	50	20	15,0	20	PA-GF / Steel
AF20.0639.0502	M6	50	20	15,0	30	PA-GF / Steel
AF20.0639.0600	M6	60	23	17,5	10	PA-GF / Steel
AF20.0639.0601	M6	60	23	17,5	20	PA-GF / Steel
AF20.0639.0602	M6	60	23	17,5	30	PA-GF / Steel

Article Code	D1	L	D	D2	L1	Material
AF20.0639.0810	M6	80	26	21,0	10	PA-GF / Steel
AF20.0839.0500	M8	50	20	15,0	10	PA-GF / Steel
AF20.0839.0501	M8	50	20	15,0	15	PA-GF / Steel
AF20.0839.0502	M8	50	20	15,0	20	PA-GF / Steel
AF20.0839.0600	M8	60	23	17,5	10	PA-GF / Steel
AF20.0839.0601	M8	60	23	17,5	20	PA-GF / Steel
AF20.0839.0602	M8	60	23	17,5	30	PA-GF / Steel
AF20.0839.0700	M8	70	25	18,0	10	PA-GF / Steel
AF20.0839.0701	M8	70	25	18,0	20	PA-GF / Steel
AF20.0839.0702	M8	70	25	18,0	30	PA-GF / Steel
AF20.0839.0810	M8	80	26	21,0	10	PA-GF / Steel
AF20.0839.0811	M8	80	26	21,0	20	PA-GF / Steel
AF20.0839.0812	M8	80	26	21,0	30	PA-GF / Steel
AF20.0839.0900	M8	90	27	22,0	10	PA-GF / Steel
AF20.0839.0901	M8	90	27	22,0	20	PA-GF / Steel
AF20.0839.0902	M8	90	27	22,0	30	PA-GF / Steel