



Description

**Material:**  
·steel, case-hardened, ground.

**Characteristics:**  
·type 1: prism part right;  
·type 2: prism part left;  
·x in the table indicates for which system the prism is suitable.

| Article Code   | L3 | d  | L2 | L  | L1 | L4 | L5 | L6 | L7 | I  | x   | Type | Material |
|----------------|----|----|----|----|----|----|----|----|----|----|-----|------|----------|
| HJ17.1206.4801 | 48 | 12 | 18 | 90 | 88 | 15 | 40 | 20 | 50 | 25 | L12 | 1    | Steel    |
| HJ17.1206.4802 | 48 | 12 | 18 | 90 | 88 | 15 | 40 | 20 | 50 | 25 | L12 | 2    | Steel    |
| HJ17.1606.5301 | 53 | 16 | 20 | 90 | 88 | 17 | 40 | 20 | 50 | 25 | L16 | 1    | Steel    |
| HJ17.1606.5302 | 53 | 16 | 20 | 90 | 88 | 17 | 40 | 20 | 50 | 25 | L16 | 2    | Steel    |

|  | D1 (mm)<br>Ø-bereik | n x T (mm)<br>afstand | x   |
|--|---------------------|-----------------------|-----|
|  | 40-330              | 1x50 = 50             | 190 |
|  | 140-430             | 2x50 = 100            | 240 |
|  | 240-530             | 3x50 = 150            | 290 |
|  | 340-630             | 4x50 = 200            | 340 |
|  | 440-730             | 5x50 = 250            | 390 |
|  | 540-830             | 6x50 = 300            | 440 |
|  | 640-930             | 7x50 = 350            | 490 |
|  | 740-1030            | 8x50 = 400            | 540 |
|  | 840-1130            | 9x50 = 450            | 590 |