



## Description

### Material:

·heat-treated steel, galvanized, chromalized.

### Characteristics:

- for levelling of machines and installations when seating areas are not parallel;
- for vertical adjustment;
- the self-locking height adjusting elements are fitted with a finepitch thread;
- all elements have a throughgoing bore for fastening purposes;
- a turn-out lock serves as height limit for the maximum adjustment height;
- additional part BB23, hook wrench for height adjustment, is available separately;
- d1 in the table shows which bolt the element is suitable for;
- L2 in the table shows the stroke (mm);
- F1(kN) in the table shows the maximum load capacity for static load;
- F2(kN) in the table shows the maximum carrying force.

Article Code	d	D	D1	d1	L	L1	L2	F1(kN)	F2(kN)	Material
BB22.0607.0250	6,6	25	M15X1,0	M6	26	22	4	40	30,7	Steel
BB22.0607.0320	6,6	32	M20X1,0	M6	31	26	5	65	55,7	Steel
BB22.0807.0320	9,0	32	M20X1,0	M8	31	26	5	65	48,0	Steel
BB22.1007.0320	11,0	32	M20X1,0	M10	31	26	5	65	37,9	Steel
BB22.1007.0450	11,0	45	M30X1,5	M10	41	34	7	120	92,9	Steel
BB22.1207.0450	13,5	45	M30X1,5	M12	41	34	7	120	80,4	Steel
BB22.1607.0450	17,5	45	M30X1,5	M16	41	34	7	120	45,5	Steel
BB22.1607.0580	17,5	58	M40x1,5	M16	53	44	9	210	136,0	Steel
BB22.2007.0580	22,0	58	M40x1,5	M20	53	44	9	210	90,0	Steel
BB22.2007.0700	22,0	70	M50x1,5	M20	60	50	10	330	210,0	Steel
BB22.2407.0580	26,0	58	M40x1,5	M24	53	44	9	210	37,0	Steel
BB22.2407.0700	26,0	70	M50x1,5	M24	60	50	10	330	157,0	Steel
BB22.0007.0700	33,0	70	M50x1,5	M30	60	50	10	330	53,0	Steel

