



## Description

### Material:

- **knob:** reinforced polyamide (PA-GF); oils and greases resistant;
- **insert:** brass right through threaded bush (tolerance 6H).

### Characteristics:

- hollow underneath hub;
- **surface:** satin;
- **color:** black (RAL 9011);
- temperature range from a minimum of -20°C to a maximum of 135°C.

### Special request:

It is possible to supply the 3 lobe handwheel hollow with female right through threaded insert in colours as shown in the table on request and for quantities.

Article Code	D	d	D1	d1	d2	d3	L	L1	L2	L3	l	l1	Material
AB58.1037.0850	85	M10	30,0	18	21,0	13,0	37	21	16	30,5	13,5	2	PA-GF / Brass
AB58.1237.0850	85	M12	30,0	18	21,0	13,0	37	21	16	30,5	13,5	2	PA-GF / Brass
AB58.0837.0850	85	M8	30,0	18	21,0	13,0	37	21	16	30,5	13,5	2	PA-GF / Brass
AB58.1037.1050	105	M10	35,0	20	25,0	23,5	46	26	19	37,5	23,0	2	PA-GF / Brass
AB58.1237.1050	105	M12	35,0	20	25,0	23,5	46	26	19	37,5	23,0	2	PA-GF / Brass
AB58.1437.1050	105	M14	35,0	20	25,0	23,5	46	26	19	37,5	21,0	2	PA-GF / Brass
AB58.1237.1250	125	M12	42,5	26	28,5	26,0	54	31	23	44,0	31,0	2	PA-GF / Brass
AB58.1437.1250	125	M14	42,5	26	28,5	26,0	54	31	23	44,0	31,0	2	PA-GF / Brass