



## Description

### Material:

- **knob:** reinforced polyamide (PA-GF); oils and greases resistant;
- **insert:** brass / stainless steel (AISI 303) blind threaded bush (tolerance 6H).

### Characteristics:

- **surface:** satin;
- **color:** black (RAL 9011);
- **temperature range** from a minimum of -20°C to a maximum of 135°C.

### Special request:

It is possible to supply colours as shown in the table on request and for quantities.

| Article Code   | D  | d   | L    | D1 | I    | Material      |
|----------------|----|-----|------|----|------|---------------|
| AB02.0437.0220 | 22 | M4  | 17,0 | 11 | 9,5  | PA-GF / Brass |
| AB02.0537.0220 | 22 | M5  | 17,0 | 11 | 8,0  | PA-GF / Brass |
| AB02.0538.0220 | 22 | M5  | 17,0 | 11 | 9,0  | PA-GF / SST   |
| AB02.0637.0220 | 22 | M6  | 17,0 | 11 | 8,0  | PA-GF / Brass |
| AB02.0638.0220 | 22 | M6  | 17,0 | 11 | 9,0  | PA-GF / SST   |
| AB02.0537.0260 | 26 | M5  | 20,5 | 13 | 15,5 | PA-GF / Brass |
| AB02.0538.0260 | 26 | M5  | 20,5 | 13 | 9,0  | PA-GF / SST   |
| AB02.0637.0260 | 26 | M6  | 20,5 | 13 | 13,0 | PA-GF / Brass |
| AB02.0638.0260 | 26 | M6  | 20,5 | 13 | 9,0  | PA-GF / SST   |
| AB02.0837.0260 | 26 | M8  | 20,5 | 13 | 13,0 | PA-GF / Brass |
| AB02.0838.0260 | 26 | M8  | 20,5 | 13 | 13,0 | PA-GF / SST   |
| AB02.0537.0320 | 32 | M5  | 24,0 | 15 | 8,0  | PA-GF / Brass |
| AB02.0637.0320 | 32 | M6  | 24,0 | 15 | 8,0  | PA-GF / Brass |
| AB02.0638.0320 | 32 | M6  | 24,0 | 15 | 14,0 | PA-GF / SST   |
| AB02.0837.0320 | 32 | M8  | 24,0 | 15 | 13,0 | PA-GF / Brass |
| AB02.0838.0320 | 32 | M8  | 24,0 | 15 | 13,0 | PA-GF / SST   |
| AB02.1037.0450 | 45 | M10 | 32,0 | 21 | 13,0 | PA-GF / Brass |
| AB02.1038.0450 | 45 | M10 | 32,0 | 21 | 16,0 | PA-GF / SST   |
| AB02.1237.0450 | 45 | M12 | 32,0 | 21 | 17,0 | PA-GF / Brass |
| AB02.1238.0450 | 45 | M12 | 32,0 | 21 | 15,0 | PA-GF / SST   |
| AB02.0837.0450 | 45 | M8  | 32,0 | 21 | 13,0 | PA-GF / Brass |