



## Description

### Material:

·heat-treated steel, galvanized, chromalized.

### Characteristics:

- for levelling of machines and installations;
- for vertical adjustment;
- the self-locking height adjusting elements are fitted with a finepitch thread;
- all elements have a throughgoing bore for fastening purposes;
- a turn-out lock serves as height limit for the maximum adjustment height;
- additional part BB23, hook wrench for height adjustment, is available separately;
- d1 in the table shows which bolt the element is suitable for;
- L2 in the table shows the stroke (mm);
- F1(kN) in the table shows the maximum load capacity for static load;
- F2(kN) in the table shows the maximum carrying force.

| Article Code   | d    | D  | D1      | d1  | L   | L1 | L2 | F1(kN) | F2(kN) | Material |
|----------------|------|----|---------|-----|-----|----|----|--------|--------|----------|
| BB21.0607.0250 | 6,6  | 25 | M15X1,0 | M6  | 43  | 28 | 15 | 40     | 30,7   | Steel    |
| BB21.0607.0320 | 6,6  | 32 | M20X1,0 | M6  | 55  | 35 | 20 | 65     | 55,7   | Steel    |
| BB21.0807.0320 | 9,0  | 32 | M20X1,0 | M8  | 55  | 35 | 20 | 65     | 48,0   | Steel    |
| BB21.1007.0320 | 11,0 | 32 | M20X1,0 | M10 | 55  | 35 | 20 | 65     | 37,9   | Steel    |
| BB21.1007.0450 | 11,0 | 45 | M30X1,5 | M10 | 67  | 42 | 25 | 120    | 92,9   | Steel    |
| BB21.1207.0450 | 13,5 | 45 | M30X1,5 | M12 | 67  | 42 | 25 | 120    | 80,4   | Steel    |
| BB21.1607.0450 | 17,5 | 45 | M30X1,5 | M16 | 67  | 42 | 25 | 120    | 45,5   | Steel    |
| BB21.1607.0580 | 17,5 | 58 | M40x1,5 | M16 | 86  | 54 | 32 | 210    | 136,0  | Steel    |
| BB21.2007.0580 | 22,0 | 58 | M40x1,5 | M20 | 86  | 54 | 32 | 210    | 90,0   | Steel    |
| BB21.2007.0700 | 22,0 | 70 | M50x1,5 | M20 | 106 | 66 | 40 | 330    | 210,0  | Steel    |
| BB21.2407.0580 | 26,0 | 58 | M40x1,5 | M24 | 86  | 54 | 32 | 210    | 37,0   | Steel    |
| BB21.2407.0700 | 26,0 | 70 | M50x1,5 | M24 | 106 | 66 | 40 | 330    | 157,0  | Steel    |
| BB21.3007.0700 | 33,0 | 70 | M50x1,5 | M30 | 106 | 66 | 40 | 330    | 53,0   | Steel    |

