



The power take off push button switch 145PTO with E-stop function is used primarily in agricultural machinery for safely switching the front or rear PTO shaft on and off.

- Contactless switching principle through reed technology
- Operating temperature -40°C to +85°C acc. to DIN IEC 68
- Simple installation
- Developed for harsh operating conditions with internal electronics sealed to IP67 protection class

IMAGE 1/1

stroke 13 ± 1

a

6

$\varnothing 40$

$\varnothing 28$

M30x1

SW36

15

53,5

89,5

113,5


1000 ± 30

cable 3x0,75mm²

40 ± 10

BN
BK
BU

button yellow



stroke 13 ±1

a

6

Ø 40

Ø 28

M 30 x 1

SW 36

15



51,5

87,5

110

17,5

button yellow



Product options

IMAGE 1/1

ORDERING KEY

145PT010A00	Power take-off switch 48V/0.3A/10W/VA	1m cable
145PT010B00	Power take-off switch 48V/0.3A/10W/VA	AMP Superseal connector, angled



SW36 nut included with delivery

Article characteristics

Attribute	145PT010A00	145PT010B00
Max. switching voltage	36 V DC	
Max. switching current	0.5 A	
Max. switching power	10 W	
Max. switching power	10 VA	
Contact form	NO	
Series resistor	3.9 Ohm	
Protection class, electronic	IP67 DIN EN 60529	
Operating temperature min.	-40 °C	
Max. operating temperature	85 °C	
Min. storage temperature	-40 °C	
Max. storage temperature	85 °C	
Installation	from above	
Mounting type	screwed	
Thread	M30	
Connector type	-	AMP Superseal 1.5 282105-1 3Pin
Cable type	BOY11Y PUR	-
Cable length	1 m	-