Mounting Extensions



The L series extensions are used for gripping on various levels using the same installation plate. These extensions are adjustable to different heights.


This system is especially useful for 2.5 bellows type suction cups, as height adjustment is made easier by the deflection of the suction cup.

Spring systems should be chosen, instead, for flat suction cups with low deflection.

Materials

Threaded rod and nut Brass

Screwed vacuum fitting Nickel-plated brass




Characteristics											
Models	A (1)			В	C	h	4	Ød	ØL	D	P
G1/8"-M	22	42	52	25	19	3	14	6	G1/8"-M	-	-
G1/4"-M	19	49	69	29	24	4	19	9	G1/4"-M	-	-
G3/8"-F	19	49	69	20.5	19.5	4	23	-	G3/8"-F	19	22
G3/8"-M	19	49	69	20.5	19.5	4	23	10	G3/8"-M	-	-

(1) Other lengths available on request for a minimum quantity of 10 pieces.

G1/4"-M - G1/8"-M


Straight






G3/8"-F

Straight or elbow 6x8



G3/8"-M

Straight or elbow 6x8



Note: All dimensions are in mm

ød

Please specify the part: Model + Thread + Adjustable stroke + Fitting + Suction cup fitting e.g.: L1449C68F										
1: Model	2: Thread		3: Adjustable	e stroke	4: Fittings		5: Suction cup fitting G3/8" version			
L	18	G1/8"	22 - 42 - 52	G1/8"	D46	Straight 4 x 6	F	Female		
	14	G1/4"	19 - 49 - 69	G1/4" G3/8"	D68	Straight 6 x 8	М	Male		
	38	G3/8"		G3/8"	C46	Elbow 4 x 6				
					C68	Elbow 6 x 8				
					N	Without fitting				

G3/8" extensions are compatible with the High Performance C series range of suction cups (see page 2/55).

